

_Huawei SUN2000-50KTL-M3 3-phase String Inverter 50 kW. Huawei is a leading global technology company headquartered in China. With an impressive presence in over 170 countries, Huawei has made a name for itself ...

*1 Inverter max input PV power is 40,000 Wp when long strings are designed and fully connected with SUN2000-450W-P power optimizers. *2 The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage inverter.

-50KTL-M3 ?????????????????????? PV ?? PID
??? PID ...

SOLAR.HUAWEI SUN2000-200KTL-H2 Technical Specifications Efficiency Max. Efficiency >=99.00% European Efficiency >=98.80% Input Max. Input Voltage 1,500 V Max. Current per MPPT 30 A Max. Short Circuit Current per MPPT 50 A Start Voltage 550 V MPPT Operating Voltage Range 500 V ~ 1,500 V Nominal Input Voltage 1,080 V Number of Inputs 18 ...

Rated AC Grid Frequency 50 Hz / 60 Hz 50 Hz / 60 Hz Max. Output Current 13.4 A 20 A Adjustable Power Factor 0.8 LG ... 0.8 LD 0.8 LG ... 0.8 LD Max. Total Harmonic Distortion { 3% { 3% Protection Input -side Disconnection Device Yes Yes Anti -Islanding Protection Yes Yes AC Overcurrent Protection Yes Yes DC Overcurrent Protection Fuseless Fuseless

Huawei Technologies Co., Ltd. Solar Inverter Series SUN2000-50KTL-M0. Detailed profile including pictures, certification details and manufacturer PDF

This document describes the SUN2000-50KTL/50KTL-C1 in terms of its installation, electrical connections, commissioning, maintenance, and troubleshooting. BOM numbers of the SUN2000s with user interface boards: 01073021 and 01073021-001; BOM numbers of the SUN2000s with no user interface board: 01073670 and 01073399.

Smart String Inverter For APAC, LATAM & EUROPE Technical Specifications Efficiency Curve Efficiency Max. Efficiency >= 99.03% >= 98.8% 1,500 V 6 65 A 115 A 4/5/4/5/5 550 V 500 V ~ 1,500 V 1,080 V 300,000 W 330,000 VA 330,000 W 800 V, 3W + PE 50 Hz / 60 Hz 216.6 A 238.2 A 0.8 LG ... 0.8 LD THD i < 1% (Rated) 1,048 x 732 x 395 mm <= 112 kg ...

Huawei FusionSolar. Products & Solutions. Introducing the HUAWEI SUN2000-50KTL-M3: a robust multi-string inverter ideal for C& I PV systems. Designed with four independent maximum power point trackers, this inverter ensures optimal ...

SOLAR .HUAWEI . Technical Specification. SUN2000-30KTL-M3: SUN2000-36KTL-M3: SUN2000-40KTL-M3. Efficiency; Max. Efficiency; ... 50 Hz / 60 Hz; Rated Output Current. 43.3 A; 52.0 A. 57.8 A; Max. Output Current. 47.9 A; 58.0 A. ... Any higher input DC voltage would probably damage inverter. 2. Any DC input voltage beyond the operating voltage ...

%. Input. Item. SUN2000-75KTL-C1. SUN2000-70KTL-C1. Maximum input power. 84,200 W. 78,600 W. Maximum input voltage a. ... If the input voltage exceeds the threshold, the solar inverter may be damaged. Note b: If the input voltage is beyond the operating voltage range, the solar inverter cannot work properly. ... 75 kW. 70 kW. Maximum ...

Rated AC Grid Frequency 50 Hz / 60 Hz Rated Output Current 76 A @380 V / 72.2 A @400 V Max. Output Current 83.6 A @380 V / 79.4 A @400 V Adjustable Power Factor Range 0.8 LG ... 0.8 LD Max. Total Harmonic Distortion <3% Protection Input-side Disconnection Device Yes Anti-islanding Protection Yes AC Overcurrent Protection Yes

The Huawei SUN2000-50KTL-M3 is a robust three-phase grid-tied string inverter designed for C& I PV rooftop plants. It efficiently converts DC power from PV strings into AC power, suitable for grid feeding or directly supplying industrial ...

%. 98.50%/400 V. 98.71%/480 V. Efficiency in China. 98.00%-European efficiency-98.24%/400 V. 98.40%/480 V. Input. Item. SUN2000-50KTL-ZHM3. SUN2000-50KTL-M3. ... Note a: The maximum input voltage is the maximum DC input voltage that the inverter can withstand. If the input voltage exceeds this value, the inverter may be damaged. Note b: If ...

Huawei FusionSolar. Products & Solutions. Introducing the HUAWEI SUN2000-50KTL-M3: a robust multi-string inverter ideal for C& I PV systems. Designed with four independent maximum power point trackers, this inverter ensures optimal performance even in complex designs, accommodating up to 8 PV strings with a maximum DC input voltage of 1100V with an rated ...

Fréquence nominale 50 Hz / 60 Hz Courant de sortie nominal 72.2 A @ 400Vac, 60.1 A @ 480Vac Courant de sortie Max 79.8 A @ 400Vac, 66.5 A @ 480Vac Facteur de puissance modifiable 0.8 LG ... 0.8LD Taux de distorsion harmonique max <3% Protection Dispositif de connexion entrée Oui Protection anti-lotage Oui

For the SUN2000 that supports built-in PID repair, when Built-in PID running mode is set to Repair, there is repair voltage between PV modules and the ground at night. If you need to ...

o This datasheet only shows Preliminary Version, the information may change. Please contact with HW local supplier for the latest version *1 The maximum input voltage is ...

This document describes the SUN2000-50KTL/50KTL-C1 in terms of its installation, electrical connections, commissioning, maintenance, and troubleshooting. BOM numbers of the ...

LTE FDD: maximum downlink rate of 150 Mbit/s and maximum uplink rate of 50 Mbit/s; LTE TDD: maximum downlink rate of 130 Mbit/s and maximum uplink rate of 30 Mbit/s; UMTS features: ...

Web: <https://bardzyndzalek.olsztyn.pl>



Outdoor Cabinet BESS
50 kWh/500 kWh Battery Storage System
Industrial and Commercial Energy Storage

All In One
Integrating battery packs

High-capacity
50 - 500kWh

Degree of Protection
IP54

Operating Temperature Range
-20~60°C(Derating above 50 °C)

Intelligent Integration
integrated photovoltaic storage cabinet

Rated AC Power
50-100kW

Altitude
3000m(>3000m derating)